

Vertical packaging machines suitable to make bags starting from a flat foil reel, combined with linear weighers. Suitable to pack granular products (short pasta, coffee, rice, legumes, dried fruit, candies, cereals, biscuits, snacks, pet food, detergent, etc.)

SPECIFICATIONS

Models	D150	D250	D350
/ Output speed*	70 bpm	50 bpm	30 bpm
Maximum bag size			
Width	280 mm	400 mm	500 mm
Length	400 mm	550 mm	750 mm
Film reel dimensions:			
Reel width max	600 mm	850 mm	1150 mm
Reel outer diam. max	400 mm	400 mm	400 mm
Reel core diam. max core	min 70 max 80 mm	min 70 max 80mm	min 70 max 80 mm
Wrapping materials	THERMOSEALING: combined or coextruded films. - THERMOPLASTIC: polyethylene monofilms.		
Film motion	Intermittent		

Options

Packaging machine: Stainless steel execution, printer, impulse seal system, flat bottom device, gas injection, 3-holes handle, etc.

Product Feeding Systems Ground hoppers, elevator belts with laths, conveyor belts, rotary tables, etc.

* The maximum running speed will depend on the product, the weight, and the in-feed condition of the product.

WEIGHTERS SPECIFICATIONS

Models	/1	/2	/3	/4
Linear heads	1	2	3	4
** Max. running speed	15 wpm	30 wpm	45 wpm	60 wpm

Options

Stainless steel execution, dimpled steel execution, inspection terrace, vibrators with holes (to clean the product)

** Indicative values referred to optimal working conditions, based on 500 gr dosages.

